## PATENT SPECIFICATION

(11) 1252638

38

## **NO DRAWINGS**

- (21) Application No. 16023/69 (22) Filed 27 March 1969
- (31) Convention Application No. P 17 69 062.9

(32) Filed 28 March 1968 in


(33) Germany (DT)

- (45) Complete Specification published 10 Nov. 1971
- (51) International Classification C 08 g 41/02, 51/34

(52) Index at acceptance

C3R 22Cio 22Ci2 22C27 22C33X 22C9Q 22D3DX 22L1B 22L2C1 22L3A 22L5X 22L6F 22N1A 22N1B


## (54) PLASTICISED POLYAMIDES



Compounds which contain hydroxyl, ester or amide groups (Hopfi-Müller-Wenger, 10 Die Polyamide (1954), pages 188 ff), or sulphonamides (Kunstoff Handbuch, Polyamide (1966), page 238 f), are mainly used for plasticising polyamides.

The known plasticisers however cannot be added in large concentrations, for example in amounts up to 40% by weight referred to the polyamide, since the moulding material thus thus produced is difficult to process. The best known plasticisers are exuded from the injection mouldings or extruded mouldings.

We have now found that these disadvantages can be prevented if cycloacetal alcohols or cycloketalalcohols having the general formula



in which n = 1 or 2, p = 0 or 1, m = 0 to 14 and p+m is greater than or equal to 1, R, R' and R'' denote a univalent organic radical which may if desired be substituted, R''

30 having at least three carbon atoms and R and R' also denoting hydrogen atoms and R' and R'' may also together form a ring, which have a boiling point of at least 250°C, can be used as plasticisers for polyamides.

In particular, the substituents R, R' and R' have the following meaning:

[Price 25p]

25

R is in most cases a hydrogen atom or an alkyl radical having 1 to 5 carbon atoms,

R' is a hydrogen atom, an aromatic radical or an alkyl radical having 1 to 8 carbon atoms, R'' is an aromatic radical or an alkyl radical having 3 to 10 carbon atoms.

R' and R" may together form a bivalent organic radical having 4 to 11 carbon atoms, so that the compound which is thus formed is a spiro compound.

Polyamides are understood in this context to be homopolycondensates of aliphatic, cycloaliphatic or aromatic dicarboxylic acids and diamines, as for example the polycondensation products of adipic acid, sebacic acid or terephthalic acid and hexamethylenediamine, phenylene diamine, as well as polycondensation products of amino carboxylic acids as for example ω-aminoundecane acid, or polymerisation products of lactams as for example caprolactam or laurolactam, and also copolymers or mixed polycondensates from diamines and dicarboxylic acids and/or aminocarboxylic acids and/or lactams.

The cycloketal alcohols and cycloacetal alcohols (for the production of which no protection is claimed within the scope of this application) may be obtained in a known manner (see Houben-Weyl, Methoden der organischen Chemie, Sauerstoffverbindungen, I — Teil 3 (1965), p213) by reacting a triol with an aldehyde or a ketone.

Suitable triols on which the cycloacetal alcohols or cyclo ketal alcohols are based are for example glycerol, hexanetriol-1,2,6, hexanetriol-1,3,6 and 1,1,1-trimethylol propane.

Aldehyde components which may be used in the cycloacetal alcohols are for example: n-butyraldehyde, isobutyraldehyde, 2-ethylcaproaldehyde, benzaldehyde, m-tolualdehyde, p-tolualdehyde, o-chlorobenzaldehyde, p-thlorobenzaldehyde, salicylaldehyde, m-hydroxybenzaldehyde, p-hydroxybenzaldehyde, o-methoxybenzaldehyde and anisaldehyde.

Suitable ketone components in the cycloketal alcohols are for example: pentanone-(2), hexanone-(2), hexanone-(3), methyl-t-butyl-



55

60

70.

75

RΛ


_			
	ketone, diisopropylketone, diisobutylketone undecanone-(6), acetophenone, benzophenone mesityl oxide, cyclopentanone, cyclohexanone	methyl - dioxan(1,3)	
.5	cyclododecanone.	hydroxymethyl - dioxan(1,3)	
	2,2 - pentamethylene - 4 - hydroxymethyldioxolane - (1,3) 2 - isopropyl - 4 - hydroxymethyldioxolane -	They are used as primary plasticisers.  The plasticisers are added to the homopoly-	
10		tional manner. For this purpose the poly-	7
15	2 - methyl - 2 - phenyl - 4 - hydroxymethyl- dioxolane - (1,3)	ketol alcohol below the softening point of the polyamide in a suitable mixer, and are then immediately processed above the softening	
	(1,3) 2,2 - diphenyl - 4 - hydroxymethyldioxolane - (1,3)	temperature of the polyamide into finished parts or semi-finished parts in a processing machine adapted for this purpose, or are	8
20	2,2 - undecamethylene - 4 - hydroxymethyl-	extruded in a suitable extruder above the softening temperature of the polyamide, after mixing, and granulated again. The cyclo-	8
	dioxolane - (1,3)  2,2 - pentamethylene - 4 - (4' - hydroxy - n - butyl) - dioxolane - (1,3)	acetal alcohols or cycloketal alcohols may also be metered into the melt in the extruder. The cycloacetal alcohols or cycloketal alco-	
25		hols can also be added to a polyamide solu- tion on account of their good compatibility with almost all organic solvents. This solution	90
30	butyl) - dioxolane(1,3) 2 - methyl - 2 - phenyl - 4 - (4' - hydroxy - n - butyl) - dioxolane(1,3)	is then processed by means of suitable pro- cessing machines and the solvent is removed from the finished article in the usual manner.	
	2 - phenyl - 4 - (4'hydroxy - n -butyl) - dioxolane(1,3) 2,2 - diphenyl - 4 - (4'hydroxy - n - butyl) -	In the case of homopolyamides the cyclo- acetal alcohols or cycloketal alcohols are gener- ally used in amounts of 5 to 40% by weight	95
35	dioxolane(1,3)  2,2 - undecamethylene - 4 - (4' - hydroxy - n - butyl) - dioxolane(1,3)	based on the weight of the homopolyamide, and in the case of copolyamides in amounts of 5 to 30% by weight based on the weight of	10
	2,2 - diisopropyl - 4 - (4' - hydroxy - n - butyl) - dioxolane(1,3) 2,2 - pentamethylene - 4 - (3' - hydroxy-	If desired, the cycloacetal alcohols or cyclo- ketal alcohols may also be used in admixture	
40	propyl) - dioxan(1,3)  2 - isopropyl - 4 - (3' - hydroxypropyl) - dioxan(1,3)	with known plasticisers in all proportions.  Plasticised polyamides which contain cycloacetal alcohols or cycloketal alcohols as plasticated alcohols are proportions.	105
45	2 - n - heptyl - (3') - 4 - (3" - hydroxy- propyl) - dioxan(1,3) 2 - methyl - 2 - phenyl - 4 - (3' - hydroxy-	iser have a particularly good thermal stability under load and toughness under cold condi- tions. In particular, these products have the	
	propyl) - dioxan(1,3) 2 - phenyl - 4 - (3' - hydroxypropyl) - dioxan(1,3) 2 - dioxan(1,3)	concentrations and the polymers thus plastic- ised can be thermoplastically processed. Poly-	110
50	2,2 - diphenyl - 4 - (3' - hydroxypropyl) - dioxan(1,3) 2,2 - undecamethylene - 4 - (3' - hydroxy-	amides produced using the hitherto known plasticisers cannot be processed by extrusion and injection moulding if they have a high	115
	propyl)dioxan(1,3)  2,2 - diisopropyl - 4 - (3' - hydroxypropyl)- dioxan(1,3)	amount of plasticiser.  The result obtained using the cycloacetal alcohols or cycloketal alcohols in accordance	
55	2,2 - pentamethylene - 5 - ethyl - 5 - hydroxy- methyl - dioxan(1,3) 2 - isopropyl - 5 - ethyl - 5 - hydroxymethyl -	plasticisers.	120
60	dioxan(1,3) 2 - n - heptyl - (3') - 5 - ethyl - 5 - hydroxy- methyl - dioxan(1,3)	Example In each case 10 kg of polylaurolactam in granule form and 2.5 kg of the plasticiser	
	2 - methyl - 2 - phenyl - 5 - ethyl - 5 - hydroxymethyl - dioxan(1,3) 2 - phenyl - 5 - ethyl - 5 - hydroxymethyl -	mixer and continuously fed to a double screw extruder. The mixture is plasticised and	125
	dioxan(1,3)	granulated at 200 to 250°C.	

2 .

thyt-			tamerhol-		Comp	Comparison Examples	les
in 53 452 230  53 455 220  1 stress 53 455 30  20°C 53 453  20°C no bending	Pen- 2-Iso- ethy- propyl 4-hyd- 4-hydroxy- methyl- methyl- 1,3- olane dioxolane	2-Methyl- 2-phenyl- 4-hydroxy- methyl- 1,3- dioxolane	len-5- ethyl-5- hydroxy- methyl- 1,3- dioxan	2-Methyl- 5-ethyl- 2-phenyl- 5-hydroxy- methyl-1,3- dioxan	Benzol- sulfon- N- methyl-	Toluol- sulfon- säure-	Tolylaurin- lactum ohne
1 stress 53 455 · 220 1 stress 53 455 30 safter 53 456 350 20°C 53 453 20°C no bending 20°C	230 220	230	230	240	230	250	800
1 stress 53 455 30  1 after 53 456 350  20°C 53 453 no bending 20°C 20	220 230	210	210	220	220	230	530
1 after 53 456 350 50 50 53 453 50 50 50 50 50 50 50 50 50 50 50 50 50	30 30	30		30	25	30	<u> </u>
20°C	20 360	350	360	370	350	350	G 001
20°C no bending ± 0°C						3	
	nding no bending	no bending 80%	no bending 17	no bending 10	no bending 12	no bending	11°
	5,9 4,3	no bending 6,3			4,5	3,0	· œ
-40°C 3,2	3,1	2,5	2,5	2,6	2,0	23	
1 mm bending of a small standard test bar under 18.5 kp/cm³ — 109		115	108	105	108	. 01	
plasticiser exudate in none injected moulded parts	ne none	none	поре	none	strong	slight	1.

WHAT WE CLAIM IS:—

 A process for plasticising a polyamide which comprises mixing the polyamide with a plasticiser comprising a cycloacetal alcohol or cycloketal alcohol of the general formula:



in which n = 1 or 2, p = 0 or 1, m = 0 to 14 and p+m ≥ 1, R, R' and R" each independently denote a monovalent organic radical which may be substituted, wherein R" contains at least three carbon atoms, R and R' may also be hydrogen atoms and R' and R' may also together form a ring, having a boiling point of at least 250°C.

 A process as claimed in claim 1 in which any organic radicals denoted by R, R' or R" or by R' and R" together are hydrocarbon radicals.

3. A process as claimed in claim 1 or 2 wherein each R independently denotes a hydrogen atom or an alkyl radical having 1 to 5 carbon atoms.

A process as claimed in claim 1, 2 or 3 wherein R' denotes hydrogen or an alkyl radical having 1 to 8 carbon atoms.

5. A process as claimed in claim 1, 2 or 3 wherein R' denotes an aromatic radical.

6. A process as claimed in claim 1, 2, 3, 4 or 5 wherein R" denotes an aromatic radical.
7. A process as claimed in claim 1, 2, 3, 4

or 5 wherein R" denotes an alkyl radical having 3 to 10 carbon atoms.

8. A process as claimed in claim 1, 2 or 3 wherein R' and R'' together denote a divalent radical having 4 to 11 carbon atoms, which together with the carbon atom to which it is attached, forms a ring.

9. A process as claimed in claim 3 in which the plasticiser is derived notionally or actually from the condensation of an aldehyde or ketone listed herein with a triol.

10. A process as claimed in claim 2 or 9 in which the plasticiser contains not more than 19 carbon atoms.

11. A process as claimed in claim 2, 9 or 10 in any of claims 3 to 8 as appendant to claim 2, in which all the Rs in the radical denoted by  $(CR_2)_m$  denote hydrogen, and the other Rs each independently denote hydrogen or an alkyl radical of 1 to 5 carbon atoms.

12. A process according to any of claims 1 to 11, wherein a cycloacetal alcohol or cycloketal alcohol is added to a polyamide in an amount of 5 to 40% by weight.

13. A process according to any of claims 1 to 12, wherein a known plasticiser is mixed with the cycloacetal alcohol or cycloketal alcohol.

14. A process for plasticising polyamides substantially as hereinbefore described.

15. A composition comprising a known plasticiser for polyamides, and a plasticiser as specified in any of claims 1 to 11.

16. A plasticised polyamide when prepared by a process as claimed in any of claims 1 to 14.

J. Y. & G. W. JOHNSON, Furnival House, 14—18 High Holborn, London, W.C.1. Chartered Patent Agents, Agents for the Applicants.

Printed for Her Majesty's Stationery Office by the Courier Press, Learnington Spa, 1971.
Published by the Patent Office, 25 Southampton Buildings, London, WC2A 1AY, from which copies may be obtained.